



## FILM FACED PREMIUM RIOPLY

### TECHINICAL SPECIFICATION

**Description:** The FILM FACED PLYWOOD RIOPLY is assembled with selected veneers following a strict quality control that results in a high quality product based on international standards. It is coated with imported Tego Film 180-gr./m<sup>2</sup>. This product is submitted to a rigorous calibration process, which grants it uniform thickness all throughout the panel. A rubberized paint is applied on the edges conferring them a highly sealing resistance. It makes RIOPLY Panels totally waterproof.

**Application:** The FILM FACED RIOPLY is indicated to use as concrete shuttering in buildings such as concrete slabs, beams, pillars/columns and foundations.

**Number of Uses:** FILM FACED RIOPLY holds out at least 25 continuous uses, once applied according to the recommended applications.

<b>DIMENSIONS</b>	2440x1220mm	2500x1250mm	
<b>THICKNESS AND NUMBER OF PLYS</b>	12mm 05/07 Plys	15mm 07/09 Plys	18mm 09/11/13 Plys

**BONDING  
(GLUEING)** Phenolic Bonding – WBP with low formaldehyde emission and 100% waterproof in accordance to EN 314 Bonding Class 3 standards (European) and PS 1-09 (American).

**DENSITY** 590 kg p/m<sup>3</sup>

**TYPE (SPECIES)** Pinus Elliottii/Taeda